Packaging

1 Per Box Locks: 1/1 set per box Keeps:

Material Specification

Lock Case:	Galvanised Mild Steel
Faceplate:	Mild Steel Zinc & Clear Passivate
Keeps:	Mild Steel Zinc & Clear Passivate
Hook and Latch:	Zinc Alloy Casting

Maintenance

To ensure performance in accordance with BS EN 1125 the following routine maintenance checks should be undertaken at regular intervals. Please refer to the Maintenance booklet for further information.



10 Year Mechanical Guarantee

Delivering peace of mind from the world's favourite lock company

CE Marked

Conforms with health, safety, and environmental protection standards



1125

Meeting the latest standards provides peace of mind for your customers

The Yale Lockmaster panic door gearing system has been independently tested to ensure that it meets the latest hardware standards. Recognised throughout Europe, this standard ensures that the Yale Lockmaster panic door gearing will deliver the right performance when you need it most.

EN112	5 Clas	sificati	ion						
3	7	6	0	1	4	2	1	Α	Α

THE YALE BRAND, with its unparalleled global reach and range of products, reassures more people in more countries than any other consumer locking solution

THE ASSA ABLOY GROUP is the world's leading manufacturer and supplier of locking solutions, dedicated to satisfying end-user needs for security, safety and convenience.

© Yale, May 2018

Yale

School Street, Willenhall, West Midlands WV13 3PW, UK T: 01902 366800 F: 01902 369041 www.yaledws.co.uk

Due to a continuous programme of development the company reserves the right to make alterations without notice. (Products which are not a stocked item will be subject to a longer lead time which needs to be agreed with your Yale representative).

*Terms and conditions apply. Please see yaledws.co.uk for further details.

Lockmaster[®] Panic Exit Device

High performance, easy exit.



- Designed specifically to work with Yale Lockmaster
- 10 year mechanical guarantee



ASSA ABLOY

Escape fast with the **Lockmaster**[®] multi-point panic door lock

Panic hardware offers rapid escape in an emergency situation, and is suitable for public areas and places where a panic situation could rapidly develop in a crisis.

The Lockmaster panic door system from Yale offers the advantages of high performance security and compression.

Designed specifically to work with Lockmaster multi-point door locks, the Lockmaster panic door is a flexible accredited system offering emergency egress capability for a wide range of applications.


- Fully compliant with EN1125
- Designed specifically to work with Lockmaster
- Unique external access system
- ICIM accredited performance
- For use in conjunction with one piece keeps
- 10 year guarantee
- Patented double door solution



Specifications

- Suitable for use in high frequency applications
- Tested to 200,000 cycles
- For use with doors up to 200kg
- Safe to use on escape route doors
- High corrosion resistance (240hrs NSS)
- Grade security level 1000N
- Standard horizontal bar projection up to 150mm
- A 'push bar' type A panic device





Applications

- For use with outward opening single and double exit doors
- Suitable for use on PVC, composite, timber and metal doors
- For doors in buildings accessed by the public where panic can be foreseen

Support available

OCKMAST



Available at www.yaledws.co.uk and YouTube



End user videos

Available at www.yaledws.co.uk and YouTube



Easy to follow installation guide/booklet

Maintenance

Ongoing maintenance guidance and record log